

QZG1256fQ

Quad Band Multi GNSS Antenna

- ▽Signal : GPS(L1,L2,L5),GLONASS(L1,L2,L3),Galileo(E1,E5,E6)
BeiDou(B1,B2,B3),QZSS(L1,L2,L5,L6)
- ▽Size : φ140.0mm × 46.5mm
- ▽Weight : 270g typ
- ▽Connector : Waterproof Connector
(TNC-Female Compatible)
- ▽Mounting : 5/8-11 UNC-2B



[Top view]



[Side view]

QZ Series

GNSS ANTENNA LINEUP

Model	GNSS Signal															
	GPS/QZSS			QZSS	GLONASS			Galileo				BeiDou				SBAS
	L1	L2	L5	L6	L1	L2	L3	E1	E5a	E5b	E6	B1	B2a	B2b/B2I	B3	L1
QZG1a	○				○			○				○				○
QZG1aD	○				○			○				○				○
QZG12aQ	○	○			○	○		○		○		○		○		○
QZG12fQ	○	○			○	○		○		○		○		○		○
QZG15 (ES)	○		○					○	○			○	○			○
QZG1256fQ	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

GNSS ANTENNA + Receiver Unit LINEUP

Model	GNSS Signal															
	GPS/QZSS			QZSS	GLONASS			Galileo				BeiDou				SBAS
	L1	L2	L5	L6	L1	L2	L3	E1	E5a	E5b	E6	B1	B2a	B2b/B2I	B3	L1
RJF9P2	○	○			○	○		○		○		○		○		○


QZG1256fQ

Signal		
Band	GPS	L1,L2,L5
	QZSS	L1,L2,L5,L6
	GLONASS	L1,L2,L3
	Galileo	E1,E5,E6
	BeiDou	B1,B2,B3
	SBAS	L1

Electrical	
Antenna Gain (Zenith)	$\leq 4.0\text{dBic}$
LNA Gain	$\leq 35\text{dB}$
Bandwidth	1590 \pm 30MHz typical 1225 \pm 60MHz typical
Out of Band Rejection	1590 \pm 100MHz $\geq 50\text{dB}$ 1225 \pm 120MHz $\geq 50\text{dB}$
Noise Figure	$\leq 2.0\text{dB}$
Voltage	+3.0~+12.0VDC
Current	$\leq 35\text{mA}$
VSWR	≤ 2.0

Mechanical	
Dimensions	$\phi 140.0\text{mm} \times 46.5\text{mm}$
Connector	QTNC Female (TNC Compatible)
Weight	270g typ
Mounting	5/8-11UNC-2B

Environmental	
Temperature	-40~+85°C
Vibration	3 axis、sweep=15min 10 to 200Hz sweep:3G
Shock	Vertical axis:50G、other axes:30G
Waterproofing	JIS C 0920 IP67
Salt Fog	MIL-STD-810F Section 509.4



KOMINE MUSEN DENKI CO.,LTD.

251 KUJI, TAKATSU-KU
KAWASAKI-SHI, KANAGAWA-KEN JAPAN 213-0032

PHONE: +81-4-4844-5522

FAX : 044-822-7224

URL : <http://www.kominemusen.co.jp>

E-Mail: info@kominemusen.co.jp

